



AcouPlex: A Composite Material Approach to Broadband Vibration Dissipation in High-Resolution Audio Systems

April 2026

Michael Preuss

Professor of Materials Science, Monash University.

In high-resolution audio systems, the limiting factor is often no longer the quality of the electrical signal path, but the degree to which that signal is preserved in the presence of mechanical disturbance. Vibrational energy, originating from loudspeakers, transformers, environmental sources, and even internal component operation, can couple into sensitive electronics and introduce subtle but cumulative distortions. These distortions rarely manifest as obvious artifacts; instead, they appear as a reduction in clarity, timing precision, and harmonic coherence. The role of a support structure, therefore, is not merely to provide mechanical stability, but to manage vibrational energy in a way that prevents storage, reflection, and delayed release. The effectiveness of AcouPlex can be understood through this lens: it is a material engineered not to block vibration, but to dissipate it efficiently across a wide frequency range.

At the heart of AcouPlex is its identity as a multi-phase composite material. Rather than relying on a single substance with a single dominant property, it combines a viscoelastic acrylic matrix with a finely ground composite that includes polyether ether ketone (PEEK), graphite, and polytetrafluoroethylene (PTFE). Each of these constituents contributes a distinct mechanical behaviour, and it is the interaction between them, rather than any one component alone, that gives rise to the material's performance.

Acrylic, which forms the structural base of the composite, provides a viscoelastic foundation. Unlike rigid materials such as metals, which tend to store vibrational energy and release it over time as ringing, acrylic exhibits internal friction at the molecular level. When subjected to vibration, it undergoes microscopic deformation, and in doing so converts a portion of that mechanical energy into heat. This behaviour is essential, as it ensures that energy entering the material is not simply reflected or retained.

However, a purely viscoelastic material can be too compliant, particularly at higher frequencies, where it may fail to provide sufficient structural control. This is where PEEK plays a critical role. As a high-performance engineering polymer with significantly greater stiffness than acrylic, PEEK reinforces the composite, extending its effectiveness into higher-frequency domains. It ensures that the material does not behave as a soft absorber but rather maintains a controlled mechanical impedance across a broad spectrum. In effect, PEEK helps the material resist deformation while still participating in energy dissipation, creating a balance between rigidity and damping.

Graphite introduces a different mechanism altogether. Its layered crystalline structure allows for microscopic slip between planes, which becomes a source of frictional energy loss when vibrational energy is present. Within the composite, graphite particles act as sites of energy scattering and dissipation. They disrupt the formation of coherent resonant modes and contribute to the breakdown of vibrational energy into smaller, less organized components. This process reduces the likelihood that energy will accumulate at specific frequencies and later re-emerge as coloration or smearing.

PTFE, commonly known as Teflon, further enhances this effect by facilitating micro-scale movement between the different phases of the composite. Its extremely low coefficient of friction allows adjacent particles and regions within the material to move slightly relative to one another under vibrational excitation. This movement, though minute, is sufficient to generate shear forces at the interfaces between materials. These forces convert mechanical energy into heat through friction and deformation, adding yet another pathway for energy dissipation.

The true effectiveness of AcouPlex emerges from the way these materials interact within a heterogeneous structure. When vibrational energy enters the material, it does not propagate uniformly. Instead, it encounters a complex landscape of differing densities, stiffnesses, and damping characteristics. Each interface between materials represents a mismatch in mechanical impedance, causing partial reflection and redirection of the energy. Rather than traveling as a coherent wave, the vibration is scattered into multiple directions and broken into smaller, less organized modes. This process, often referred to as mode fragmentation, prevents the formation of dominant resonances and significantly reduces the storage of energy within the material.

At the same time, the multitude of internal interfaces creates opportunities for micro-shear and frictional losses. As the different phases respond to vibration in slightly different ways, they move relative to one another at a microscopic level. This relative motion is where much of the energy conversion occurs, as mechanical energy is dissipated as heat through repeated cycles of deformation and friction. Because these mechanisms operate across a wide range of frequencies and scales, the material is capable of broadband damping rather than being tuned to a narrow band.

This distinguishes AcouPlex from simpler approaches to vibration control. Rigid materials, such as metals, tend to reflect and store energy, leading to resonant behaviour that can interfere with signal integrity. Soft materials, such as rubber or elastomers, may absorb energy effectively at certain frequencies but often do so at the expense of dynamic responsiveness and high-frequency control. AcouPlex occupies a middle ground, combining sufficient stiffness to maintain structural integrity with enough internal damping to prevent energy storage. The result is a material that dissipates vibration without introducing sluggishness or loss of energy in the audible domain.

In practical terms, the reduction of mechanical vibration manifests in several ways within an audio system. Lower levels of vibration reduce microphonic interactions within components, particularly in sensitive circuits such as digital clocks, analogue stages, and power supplies. This leads to a lower effective noise floor, allowing low-level detail to emerge more clearly. At the same time, the reduction of energy storage and delayed release improves temporal accuracy. Transients become more precisely defined, and the subtle timing relationships that underpin musical coherence are preserved. Harmonic structures, which depend on the accurate reproduction of complex overtone relationships, become more distinct and less prone to blurring. Spatial information, which relies on phase stability, is also improved, resulting in a more stable and believable soundstage.

What is particularly notable is that these improvements do not come at the expense of musical energy or engagement. Because AcouPlex does not rely on heavy damping or isolation through compliance alone, it avoids the common trade-off between control and liveliness. Instead, it preserves the dynamic integrity of the system while removing sources of interference. This balance is a direct consequence of its composite nature and the multiple dissipation mechanisms operating simultaneously.

In this sense, the effectiveness of AcouPlex lies not in any single property, but in the synergy between its components. It is a material that manages vibrational energy through a combination of viscoelastic damping, impedance mismatch, energy scattering, and interfacial shear. By addressing vibration at multiple scales and across a wide frequency range, it achieves a level of control that is difficult to replicate with more homogeneous materials.

Ultimately, AcouPlex demonstrates that in high-resolution audio systems, mechanical design is inseparable from sonic performance. By converting unwanted vibrational energy into heat before it can interfere with the signal, it allows the system to operate closer to its intrinsic potential. The result is not a change in tonal character, but a reduction in distortion, revealing greater clarity, coherence, and realism in the reproduced sound.